



BCI™ 3301 HAND-HELD PULSE OXIMETER

THE BCI ADVANTAGE

- Durable yet lightweight design
- Ergonomically designed to fit your hand comfortably
- Bright, easy-to-read LED numerals
- Quantitative pulse strength bar on screen
- Fast, reliable SpO₂ & pulse rate measurements
- Stores data for up to 99 different patients
- Simple On/Off control with auto shutoff to conserve battery life
- Powered by 3 easily replaceable C-cell batteries
- Monitor patients ranging from neonate to adult
- Genuine BCI, Inc. reusable & disposable sensors available



Simple, accurate
spot-checking from
the hand-held
pulse oximetry
leader.

The **BCI™ 3301 HAND-HELD PULSE OXIMETER** quickly and reliably delivers pulse oximetry wherever spot-checking is needed... including EMS, physicians offices, outpatient clinics and hospitals. In fact, its ergonomic design, easy-to-read display and proven ability to accurately indicate SpO₂ and pulse rate for patients from neonate to adult have helped make BCI, Inc. the global leader in hand-held pulse oximetry technology. For more information, visit smiths-bci.com.

smiths
Smiths Medical – a part of Smiths Group plc

BCI™ 3301 HAND-HELD PULSE OXIMETER

SPECIFICATIONS:

Displays, Indicators, & Keys:

SpO ₂	LED numeric display 0.43 inch (10.9mm) high
Pulse Rate	LED numeric display 0.300 inch (7.62mm) high
Pulse Strength	Logarithmically scaled, 8-segment bargraph
Keys	ON & OFF Keys

SpO₂:

Range	0-99%
Accuracy	±2% at 70-99%; <70% unspecified
Averaging	8 beat average

Pulse Rate:

Range	30-254 bpm
Accuracy	±2% at 30-254 bpm
Averaging	8 second average

Memory:

1,000 Spot Checks, up to 99 patients

Dimensions:

6.3" H x 3.25" W x 1.25" D
160mm x 82.6 mm x 31.75mm

Weight:

16.5 oz. (462 grams) with batteries

Power Requirements:

(3) "C" Cell Alkaline or NiCAD Batteries

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE

Please read the Instructions for Use supplied with the product for detailed instructions, warnings, and cautions.

Battery Life:

Approximately 24 hours in Continuous Use Mode.
1500 spot checks, 1 min. on, 2 min. off

Auxiliary Printer Output:

RS232C

Environmental Specifications:

Operating Temperature	32°F to 131°F [0°C to 55°C]
Storage Temperature	-29°F to 158°F [-34°C to 70°C]
Relative Humidity	10-95% (storage) 15-95% (operating)

Mechanical Durability Test Results:

Vibration Testing	In compliance with MIL-STD-810E, Method 514.4 IEC 68-2-6, IEC 68-2-34
Shock Testing	In compliance with IEC 68-2-27
Drop Testing	Exceeded UL 544 testing recommendations

Standards:

EN60601-1 (IEC 601-1)
UL 2601-1 and CAN/CSA 601.1
CAN/CSA NRTL/C

Regulatory Compliance:

510(k): K943404, K980714



CE 0473

ISO 9001 / EN46001

Catalog Number: 3301

MDD version available

Q-Line for U.S.A. Customers call 1-800-348-1842 for emergency and clinical application information 24 hours a day, 365 days a year. Experienced Clinical Specialists will return your call and assist with any questions you may have.

For more information or for the name of your representative, contact BCI, Inc.



BCI, Inc., N7 W22025 Johnson Road, Waukesha, Wisconsin 53186 USA
Phone: 262-542-3100 Fax: 262-542-0718 Toll-Free: 800-558-2345
e-mail: info@smiths-bci.com Internet: http://www.smiths-bci.com

The product described is covered by U.S. Patent No. 351,023
BCI and BCI design are BCI, Inc. trademarks
The symbol ® indicates it is registered in the U.S. Patent and Trademark Office and certain other countries.
Smiths is a registered trademark of Smiths Group plc
© 2002 BCI, Inc. All rights reserved BCI 3301-09 0802

smiths
Smiths Medical - a part of Smiths Group plc



BCI, Inc. - The world leader in hand-held pulse oximetry technology; Part of the Smiths Medical Group - your source for BCI, Deltec, Level 1, and Portex technologies.