

# AUTO\* THERM<sup>®</sup> 395

## Specifications

Input:	230 VAC ± 10% or 115 VAC ± 10%, 50–60 Hz,
Safety Standard	Class I
CE mark	CE 0197 for conformity with Directives 93/42/EEC-MDD and 89/336/EMC
Classification	MDD class IIa
Weight:	~40 kg
Dimensions:	85 cm (H) x 38 cm (W) x 38 cm (D)
Frequency:	27,12 MHz
HF peak output:	400 W
Pulse frequency:	70 Hz / 350 Hz
Pulse duration range:	2 ms / 0,4 ms

## Accessories

Coil field set *	1 four-joint folding arm 1—14 cm diameter coil applicator 1 special field coil cable
Condenser field set *	2 four-joint folding arms 2—13 cm diameter condenser applicators 2 cables for condenser applicators
Plate applicator set 1	2—8 x 14 cm soft-rubber plate applicators with flexible cables 6 felt spacers 2 cloth covers 2 perforated rubber bands with buttons
Plate applicator set 2	2—12 x 18 cm soft-rubber plate applicators with flexible cables 6 felt spacers 2 cloth covers 2 perforated rubber bands with buttons

\* *It is recommended to select either the coil or condenser field set to accompany the basic unit.*

## Applicators

- 8 cm diameter coil applicator without cable
- 14 cm diameter coil applicator without cable
- 15 x 35 cm Triplode coil applicator with cable
- 4.2 cm diameter condenser applicator
- 8.5 cm diameter condenser applicator
- 13 cm diameter condenser applicator
- 8 x 14 cm soft-rubber plate applicator complete with flexible cable
- 12 x 18 cm soft-rubber plate applicator complete with flexible cable

