

EDANUSA

www.edanusa.com

VE-H100B

Veterinary Pulse Oximeter



Easy Operation

300 h
SpO₂ Review

100
ID Storage



Large/Small Size Sensors



Battery Charger Stand



Care for Health

VE-H100B

Veterinary Pulse Oximeter

Mounting Solutions



Bed Rail Mount



Carrying Bag



Charger Stand

- LCD display with backlight control
- Dual work modes: monitoring & spot check
- Numeric display with plethysmogram display
- Trend review
- Pulse-tone modulation (Pitch Tone)
- Adjustable audio and visual alarms
- Powerful data storage capacity (up to 300 hours)
- PatientCare Viewer software for PC data management
- 4 x AA batteries for up to 48 hours of work
- Rechargeable battery for up to 30 hours of work
- Optional battery charger stand
- Automatic power-off function for power saving
- Suitable for dogs, cats and other animals

Specification

Classification

Type of Protection	Internally power equipment (on battery power)
EMC Compliance	Class B
Degree of Protection	Type BF-Applied Part
Mode of Operation	Continuous
Enclosure Degree of Ingress Protection	IPX2

Size and Weight

Size	160 (L)x70 (W)x37.6 (H) (mm)
Weight	165 g (without batteries)

Environment

Temperature	
Working	5 C~40 C
Storage/Shipping	-20 C~55 C
Humidity	
Working	25%~80% (Non-condensing)
Storage/Shipping	25%~93% (Non-condensing)

Display

VE-H100B	LCD (128*64)
----------	--------------

Charger Stand

Input Voltage	100 to 240V AC, 50/60 Hz
Output Voltage	8 V DC
Output Current	0.8 A
Output Power	6.4 W

Battery

Ni-MH Rechargeable Battery Package	
Quantity	1
Total Rated Voltage	4.8 V
Capacity	1800 mAh
Typical Battery Life	30 hours
Charge Time	2.5 hours to 80% 4 hours to 100%
Alkaline Batteries	
Typical Battery Life	48 hours (4 x AA batteries)

Measuring Parameter Specification

Measurement Range	
SpO ₂	0-100%
PR	30-254 bpm
SpO ₂ Resolution	1%
PR Resolution	1 bpm