

# COMeNUS

## C80 ICU Monitor



- CardioTec™ 12-lead ECG, Masimo SpO<sub>2</sub>, AcuTec™ NIBP, RESP, TEMP, 12.1" TFT touch screen, handwriting pen, EtCO<sub>2</sub> socket, Li-ion battery.
- Option: Dual IBP, EtCO<sub>2</sub>, AG, ICG, C.O., thermal printer, IoC, pediatric Neonatal accessories.
- IPX1 level waterproof design.
- I-KLOK™ intelligent alarm management for all parameters, auto-identification for alarm level.

## C60 NICU Monitor



- Considering the feature of neonatal HR, we adopt the latest ExNeo™ technology to guarantee the accuracy of measurement.
- World leading SpO<sub>2</sub> technology, Masimo SpO<sub>2</sub>.
- SatSeconds™ intelligent alarm management technology to reduce false alarms, accurate patient information transfer.
- Considering the low blood and low perfusion feature of neonate, we adopt Adap-DSP™ system to provide more accurate measurement.
- Unique neonate measurement mode, soft & hard over-pressure protection.
- Bio-compatibility approved accessories for neonate.



# C50

## Multi-parameter Patient Monitor

ComenUS

4901 Morena Blvd., Suite 505  
San Diego, CA 92121  
info@comenus.com  
Tel: 888.602.7767



# C50 Multi-parameter Patient Monitor Features

- 10.4" TFT Touch Screen.
- Operating methods: Trim knob/ button, touch screen.
- Advanced patient file management system.
- High capacity storage, power-off data protection.
- Inclined screen for easy observation.
- Standard Configuration:**  
5-lead ECG, Comen SpO<sub>2</sub>, PR, NIBP, RESP, TEMP
- Optional Configuration:**  
Masimo/ Nellcor SpO<sub>2</sub>, Dual IBP, EtCO<sub>2</sub>, Thermal Printer, C.O., ICG



- Mounting solutions: vertical hanging, wall mounting, rolling stand.

- Complied with CE standards, integrated modular design and aluminum alloy structure guarantee product's safety & stability.
- High standard design, splendid appearance, best craftsmanship.



- IPX1 waterproof design, good performance in various environment.



- Fixed handle, easy to carry



- 4000mAh Li-ion battery, above 4 hours working time



- NIBP Dust shield



- Handwriting pen with slot ports: SD card, USB, Network

- I-KLOK™ Intelligent alarm management, automatic-identification of alarm level. Self-adjust proper alarm time to reduce false alarms.

- ARR analysis, RESP Apnea Alarm, OxyCRG.

- CMRR ≥ 105 dB, outstanding ECG anti-interference capability.

